

Material testing and hyperelastic material model curve fitting for Ogden, Polynomial and Yeoh models

ScilabTEC 2015, Paris, France

Michael Rackl
`rackl@fml.mw.tum.de`

Technische Universität München (TUM)
Institute for Materials Handling, Material Flow, Logistics

Ostbayerische Technische Hochschule Regensburg
Laboratory for Biomechanics

21st and 22nd May 2015

Outline

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Introduction

Background

- Static structural investigation on a silicone-suspended fracture plating system
- Modelling by means of finite element method (FEM)

⇒ How to model silicone in FEM?

Answer from literature: **hyperelastic material models**

Introduction

Hyperelastic material models

Two types of hyperelastic material models¹

Phenomenological models

material constants generated
by curve fitting

Micro-mechanical models

material constants generated
by specific material tests

The use of phenomenological model is suggested, as the physical significance of micro-mechanical material constants is often unclear².

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Fitting hyperelastic material constants

workflow and material model selection

- 1 **Material tests:** stress-stretch curves from e. g. uni- or bi-axial tensions tests, shear tests.
- 2 **Curve fitting:** adapting the material constants based on analytical models, to closely reproduce the measured curves.
- 3 **Validation** by modelling the material tests with FEM and comparison of the results.

Material models selected for this work:

- Ogden Model³,
- Polynomial Model⁴ (includes the Mooney-Rivlin Model^{5;6}),
- Yeoh Model⁷.

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Problem description and approach

FEM software *ANSYS*^a offers higher-order hyperelastic material model input, but does not feature curve fitting for each of these models.

Approach:

Create a *SCILAB*^b script and corresponding functions to conduct non-restrictive curve fitting.

^a *ANSYS* Inc., Canonsburg, Pennsylvania, USA

^b *SCILAB* ENTERPRISES, Versailles, France

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model


4 Conclusion

- General
- Discrepancies with the Ogden Model implementation



Materials and Methods

Material tests

Bonded compression/tension test (stress results to be corrected⁸⁾)



Simple shear test



all dimensions in
Millimetres;
“strip” refers to
a steel strip

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Analytical equation of the Yeoh Model in tension/compression (example) I

1. Base equation of the Yeoh Model: $W = \sum_{i=1}^n C_i \cdot (I_1 - 3)^i$

- W : strain energy,
- C_i : material constant,
- I_1 : strain invariant,
- n : model order.

2. strain invariants I_1 for compression/tension^{9;10}:

$$I_1 = \lambda^2 + 2\lambda^{-1},$$

$$I_2 = \lambda^{-2} + 2\lambda.$$

- λ : stretch due to tensile/compressive stress

Analytical equation of the Yeoh Model in tension/compression (example) II

3. relation between engineering stress σ_e and stretch λ for an incompressible material under tension/compression^{6;11}:

$$\sigma_e = 2 \cdot (\lambda - \lambda^{-2}) \cdot \left(\frac{\partial W}{\partial I_1} + \frac{1}{\lambda} \cdot \frac{\partial W}{\partial I_2} \right).$$

4. Combining the aforementioned equations yields

$$\sigma_e(\lambda) = \sum_{i=1}^n 2 \cdot C_i \cdot i \cdot (\lambda - \lambda^{-2}) \cdot (\lambda^2 + 2\lambda^{-1} - 3)^{i-1}$$

for tension/compression of an n^{th} order Yeoh Model.

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model


4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Optimisation problem

Scilab script overview

index “M” denotes data from measurement



Optimisation problem

notes

- Error criteria ϵ_σ and ϵ_τ may be normalised or unnormalised (absolute)

$$\epsilon_{norm} = \sum \left(1 - \frac{\sigma(\lambda, \vec{C})}{\sigma_M(\lambda)} \right)^2$$
$$\epsilon_{abs} = \sum \left(\sigma_M(\lambda) - \sigma(\lambda, \vec{C}) \right)^2$$

- Adjusted coefficient of determination¹² was computed for goodness of fit evaluation
- Results for lower-order material models were compared to those from ANSYS

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Results and Discussion

Ogden Model; comparison with ANSYS


Ogden models used in curve fitting and results for the material parameters in ANSYS and using the SCILAB script ($[\mu_i] = \text{MPa}$, $[\alpha_i] = 1$).

Order	error criterion	number of parameters	parameters from curve fitting routine	
			ANSYS	SCILAB script
2 nd	norm.	4	$\mu_1 = -0.1244$	$\mu_1 = 4.290$
			$\alpha_1 = 1.316$	$\alpha_1 = 0.1370$
			$\mu_2 = 0.6225$	$\mu_2 = 7.484 \times 10^{-3}$
			$\alpha_2 = 1.299$	$\alpha_2 = 4.346$
3 rd	abs.	6	$\mu_1 = 0.1770$	$\mu_1 = 28.01 \times 10^{-3}$
			$\alpha_1 = 1.055$	$\alpha_1 = 3.525$
			$\mu_2 = 0.2338$	$\mu_2 = -4.385$
			$\alpha_2 = 1.041$	$\alpha_2 = 0.7777$
			$\mu_3 = 0.3251$	$\mu_3 = 7.270$
			$\alpha_3 = 0.9889$	$\alpha_3 = 0.5449$
4 th	abs.	8	not available	$\mu_1 = 58.90 \times 10^{-3}$
				$\alpha_1 = 2.800$
				$\mu_2 = -3.552$
				$\alpha_2 = -0.3355$
				$\mu_3 = 4.380$
				$\alpha_3 = -79.13 \times 10^{-3}$
				$\mu_4 = -0.4110$
				$\alpha_4 = 0.9359$


Results and Discussion

Ogden Model; curve fitting example

Comp./Tens. results f. Ogden (8 param.)



Simple Shear results f. Ogden (8 param.)



1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Results and Discussion

Polynomial Model; comparison with ANSYS


Polynomial models used in curve fitting and results for the material parameters in ANSYS and using the SCILAB script. The model with three parameters is equivalent to a three parameter Mooney-Rivlin model. ($[C_{ij}] = \text{MPa}$).

Order	error criterion	number of parameters	parameters from curve fitting routine	
			ANSYS	SCILAB script
1 st	norm.	2	$C_{10} = 37.98 \times 10^{-3}$ $C_{01} = 0.1043$	$C_{10} = 37.98 \times 10^{-3}$ $C_{01} = 0.1043$
-	abs.	3	$C_{10} = 74.92 \times 10^{-3}$ $C_{01} = 73.71 \times 10^{-3}$ $C_{11} = -1.972 \times 10^{-3}$	$C_{10} = 74.92 \times 10^{-3}$ $C_{01} = 73.71 \times 10^{-3}$ $C_{11} = -1.972 \times 10^{-3}$
2 nd	abs.	5	$C_{10} = -88.41 \times 10^{-3}$ $C_{01} = 0.2197$ $C_{20} = 0.2122$ $C_{11} = -0.2909$ $C_{02} = 78.22 \times 10^{-3}$	$C_{10} = -88.41 \times 10^{-3}$ $C_{01} = 0.2197$ $C_{20} = 0.2122$ $C_{11} = -0.2909$ $C_{02} = 78.22 \times 10^{-3}$


Results and Discussion

Polynomial Model; curve fitting example

Comp./Tens. results f. Polynom. (2 param.)



Simple Shear results f. Polynom (2 param.)



1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Results and Discussion

Yeoh Model; comparison with ANSYS


Yeoh models used in curve fitting and results for the material parameters in ANSYS and using the SCILAB script ($[C_{i0}] = \text{MPa}$).

Order	error criterion	number of parameters	parameters from curve fitting routine	
			ANSYS	SCILAB script
3 rd	norm.	3	$C_{10} = 0.1595$ $C_{20} = -6.930 \times 10^{-3}$ $C_{30} = 0.4030 \times 10^{-3}$	$C_{10} = 0.1595$ $C_{20} = -6.930 \times 10^{-3}$ $C_{30} = 0.4030 \times 10^{-3}$
4 rd	norm.	4	not available	$C_{10} = 0.1593$ $C_{20} = -6.220 \times 10^{-3}$ $C_{30} = 0.2210 \times 10^{-3}$ $C_{40} = 11.90 \times 10^{-6}$
5 rd	norm.	5	not available	$C_{10} = 0.1573$ $C_{20} = 2.391 \times 10^{-3}$ $C_{30} = -3.907 \times 10^{-3}$ $C_{40} = 0.6600 \times 10^{-3}$ $C_{50} = -32.60 \times 10^{-6}$


Results and Discussion

Yeoh Model; curve fitting example

Comp./Tens. results f. Yeoh (4 param.)



Simple Shear results f. Yeoh (4 param.)



1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Conclusion

General

- Curve fitting script for fitting any order Ogden, any order Yeoh and second as well as first order Polynomial models, plus a three parameter Mooney-Rivlin Model.
- Yeoh and Polynomial Model curve fitting for lower-order models successfully validated against results from ANSYS
- SCILAB script allows for
 - curve fitting of higher order models than Ansys,
 - biasing of one of the material test results possible.
- higher order models tend to instabilities at small nominal-strains (ANSYS warning message)

1 Introduction

- Background information
- Fitting hyperelastic material constants
- Problem description and approach

2 Materials and Models

- Material tests
- Analytical equation for the Yeoh Model in tension/compression (example)
- Optimisation problem

3 Results and Discussion

- Ogden Model
- Polynomial Model
- Yeoh Model

4 Conclusion

- General
- Discrepancies with the Ogden Model implementation

Conclusion

Discrepancies with the Ogden Model implementation I

- Ogden Model implementation \Rightarrow difference in material constants between ANSYS and the SCILAB script
- Results for lower-order models from verification process:

Ogden models material parameters, fitted in ANSYS and using the SCILAB script ($[\mu_i] = \text{MPa}$, $[\alpha_i] = 1$).


Order	error criterion	number of parameters	parameters from curve fitting routine	
			ANSYS	SCILAB script
1 st	abs.	2	$\mu_1 = 0.7055$ $\alpha_1 = 1.0546$	$\mu_1 = 0.7208$ $\alpha_1 = 1.0345$
1 st	norm.	2	$\mu_1 = 0.5571$ $\alpha_1 = 1.1609$	$\mu_1 = 0.6356$ $\alpha_1 = 1.023$




Conclusion

Ogden Model implementation II: FEA validation result


Simple shear Test, 0.25mm samples




Comparison of force-displacement curves in simple shear




Tension Test, 3 mm samples




Comparison of force-displacement curves in tension



Compression Test, 3 mm samples



Comparison of force-displacement curves in compression



Conclusion

Discrepancies with the Ogden Model implementation III

Ogden Model appears to be implemented correctly within the SCILAB script (cf. previous slide)

Differences could arise from

- the nonlinear nature of the problem,
- the fact that more than one minimum exists.

Besides: Even identical start values may lead to completely different material parameter sets¹³.

Thank you!

Do you have questions or feedback?

References (two slides)

- [1] P. Steinmann, M. Hossain, and G. Possart. Hyperelastic models for rubber-like materials: consistent tangent operators and suitability for Treloar's data. *Archive of Applied Mechanics*, 82(9):1183–1217, 2012.
- [2] R. W. Ogden, G. Saccomandi, and I. Sgura. Fitting hyperelastic models to experimental data. *Computational Mechanics*, 34(6):484–502, 2004.
- [3] R. W. Ogden. Large Deformation Isotropic Elasticity - On the Correlation of Theory and Experiment for Incompressible Rubberlike Solids. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 326(1567):565–584, 1972.
- [4] R. S. Rivlin and D. W. Saunders. Large Elastic Deformations of Isotropic Materials. VII. Experiments on the Deformation of Rubber. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 243(865):251–288, 1951.
- [5] M. Mooney. A Theory of Large Elastic Deformation. *Journal of Applied Physics*, 11(9):582–592, 1940.
- [6] R. S. Rivlin. Large Elastic Deformations of Isotropic Materials. IV. Further Developments of the General Theory. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 241(836):379–397, 1948.
- [7] O. H. Yeoh. Some Forms of the Strain Energy Function for Rubber. *Rubber Chemistry and Technology*, 66(5):654–661, 1993.

- [8] J. M. Horton, G. E. Tupholme, and M. J. C. Gover. Axial Loading of Bonded Rubber Blocks. *Journal of Applied Mechanics*, 69(6):836, 2002.
- [9] L. R. G. Treloar. The elasticity and related properties of rubbers. *Reports on Progress in Physics*, 36(7):755–826, 1973.
- [10] F. R. Schwarzl. *Polymermechanik: Struktur und mechanisches Verhalten von Polymeren*. Springer, Berlin, 1990. p. 298-299.
- [11] R. S. Rivlin. Large Elastic Deformations. In F. R. Eirich, editor, *Rheology*, pages 351–385. Academic Press, New York, 1956.
- [12] L. Fahrmeir, T. Kneib, and S. Lang. *Regression: Modelle, Methoden und Anwendungen*. Statistik und ihre Anwendungen. Springer, Berlin and Heidelberg, 2nd edition, 2009. p. 161.
- [13] A. Zielesny. *From curve fitting to machine learning: An illustrative guide to scientific data analysis and computational intelligence*, volume 18 of *Intelligent systems reference library*. Springer, Berlin, 2011. p. 146.